

DEVICE AND METHOD FOR BROADCAST SIGNAL DEMODULATION

Publication number: JP11289503 (A)

Publication date: 1999-10-19

Inventor(s): TSUBOI SHUSUKE; AIZAWA MASAMI

Applicant(s): TOKYO SHIBAURA ELECTRIC CO

Classification:

- international: H04N5/455; H04H20/00; H04H20/74; H04N5/455; H04H1/00;
(IPC1-7): H04N5/455; H04H1/00

- European:

Application number: JP19980088981 19980401


Priority number(s): JP19980088981 19980401

Also published as:

JP4091161 (B2)

Abstract of JP 11289503 (A)

PROBLEM TO BE SOLVED: To view pluralities of broadcast signals with different transmission line coding systems at the same time. **SOLUTION:** A transmission control signal decoder 18 extracts a transmission control signal from an output of an error correction device 34. A demodulator 33 conducts demodulation processing depending on each TS based on the transmission control signal. A demodulation output from the error correction device 34 is given to a bit stream output multiplexer 15, where the output is time-division-multiplexed and information relating to a multiplex output such as a business operator code is fed to a signal changeover device 16. Thus, the signal changeover device 16 applies each TS to corresponding decoders 20, 27. Thus, pluralities of streams included in a same physical channel are viewed at the same time.



Data supplied from the esp@cenet database — Worldwide